

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 2901

Revision date: 11.04.2024

Product code: 2901

Page 1 of 13

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Kisling - 2901

UFI: EPPM-K4U3-YFFS-1GS8

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Activator

#### Uses advised against

No data available

### 1.3. Details of the supplier of the safety data sheet

#### Manufacturer

Company name: Kisling AG  
Street: Motorenstrasse 102  
Place: CH-8620 Wetzikon  
Telephone: +41 58 272 0 272  
E-mail: customerservice@kisling.com  
Internet: www.kisling.com

#### Supplier

Company name: Kisling (Deutschland) GmbH  
Street: Salzstraße 15  
Place: D-74676 Niedernhall  
Telephone: +49 7940 50961 61  
E-mail: customerservice@kisling.com  
Contact person: Dr. Hans Götz Telephone: +49 7940 5096 143  
E-mail: compliance@kisling.com  
Internet: www.kisling.com

### 1.4. Emergency telephone number:

24 hr. emergency phone number +1 872 5888271 (KAR)  
Medicines & Poisons Info Office +356 2545 6508

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Regulation (EC) No 1272/2008

Flam. Liq. 2; H225  
Eye Irrit. 2; H319  
STOT SE 3; H336  
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

### 2.2. Label elements

#### Regulation (EC) No 1272/2008

#### Hazard components for labelling

acetone; propan-2-one; propanone

Signal word: Danger

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 2901

Revision date: 11.04.2024

Product code: 2901

Page 2 of 13

#### Pictograms:



#### Hazard statements

H225 Highly flammable liquid and vapour.  
 H319 Causes serious eye irritation.  
 H336 May cause drowsiness or dizziness.  
 H412 Harmful to aquatic life with long lasting effects.

#### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P233 Keep container tightly closed.  
 P280 Wear protective gloves and eye/face protection.  
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P403+P235 Store in a well-ventilated place. Keep cool.

#### Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

#### Pictograms:



#### Hazard statements

H412

#### 2.3. Other hazards

Pressurised container: May burst if heated.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
67-64-1	acetone; propan-2-one; propanone			50 - < 100 %
	200-662-2	606-001-00-8		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
68084-48-0	Copper(2+) neodecanoate			0.1 - < 1 %
	268-439-2		01-2120784744-41	
	Acute Tox. 4, Aquatic Acute 1, Aquatic Chronic 1; H302 H400 H410			

Full text of H and EUH statements: see section 16.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 2901

Revision date: 11.04.2024

Product code: 2901

Page 3 of 13

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
67-64-1	200-662-2	acetone; propan-2-one; propanone	50 - < 100 %
		inhalation: LC50 = 76 mg/l (vapours); dermal: LD50 = > 7426 mg/kg; oral: LD50 = 5800 mg/kg	
68084-48-0	268-439-2	Copper(2+) neodecanoate	0.1 - < 1 %
		oral: LD50 = 2066 mg/kg Aquatic Acute 1; H400: M=10 Aquatic Chronic 1; H410: M=1	

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### General information

Take off immediately all contaminated clothing.

##### After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

##### After contact with skin

Wash with plenty of water. Take off contaminated clothing and wash it before reuse. After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation, consult a physician.

##### After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

##### After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth immediately and drink 1 glass of water. Get immediate medical advice/attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

No further relevant information available.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. No further relevant information available.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

##### Suitable extinguishing media

Carbon dioxide (CO<sub>2</sub>), Dry extinguishing powder, alcohol resistant foam, Water spray.

##### Unsuitable extinguishing media

Full water jet.

#### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

##### Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### General advice

Remove all sources of ignition.

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

#### 6.3. Methods and material for containment and cleaning up

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 2901

Revision date: 11.04.2024

Product code: 2901

Page 4 of 13

#### For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

#### Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

#### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13 See protective measures under point 7 and 8.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

##### Advice on safe handling

Use only in well-ventilated areas. Keep away from sources of ignition - No smoking. Flammable vapours can accumulate in head space of closed systems. Caution! Transport usually takes place at temperatures above the flash point.

##### Advice on protection against fire and explosion

Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

##### Advice on general occupational hygiene

Take off contaminated clothing. Wash hands before breaks and after work. When using do not eat, drink, smoke, sniff. Remove contaminated, saturated clothing immediately.

##### Further information on handling

Keep only in the original container in a cool, well-ventilated place.

#### 7.2. Conditions for safe storage, including any incompatibilities

##### Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

##### Hints on joint storage

Do not store together with: Material, oxygen-rich, Oxidising, Pyrophoric or self-heating substances.

##### Further information on storage conditions

Keep away from heat.

#### 7.3. Specific end use(s)

No further relevant information available.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Occupational exposure limit values

CAS No	Name of agent	ppm	mg/m <sup>3</sup>	fib/cm <sup>3</sup>	Category	Origin
67-64-1	Acetone	500	1210		TWA (8 h)	

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 2901

Revision date: 11.04.2024

Product code: 2901

Page 5 of 13

#### DNEL/DMEL values

CAS No	Name of agent		
DNEL type	Exposure route	Effect	Value
67-64-1	acetone; propan-2-one; propanone		
Worker DNEL, long-term	inhalation	systemic	1210 mg/m <sup>3</sup>
Worker DNEL, acute	inhalation	local	2420 mg/m <sup>3</sup>
Worker DNEL, long-term	dermal	systemic	186 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	200 mg/m <sup>3</sup>
Consumer DNEL, long-term	dermal	systemic	62 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	62 mg/kg bw/day

#### PNEC values

CAS No	Name of agent	
Environmental compartment	Value	
67-64-1	acetone; propan-2-one; propanone	
Freshwater	10,6 mg/l	
Freshwater (intermittent releases)	21 mg/l	
Marine water	1,06 mg/l	
Freshwater sediment	30,4 mg/kg	
Marine sediment	3,04 mg/kg	
Micro-organisms in sewage treatment plants (STP)	100 mg/l	
Soil	29,5 mg/kg	
68084-48-0	Copper(2+) neodecanoate	
Freshwater	0.04875 mg/l	
Marine water	0.0325 mg/l	
Freshwater sediment	543.75 mg/kg	
Marine sediment	4225 mg/kg	
Secondary poisoning	20 mg/kg	
Micro-organisms in sewage treatment plants (STP)	1.44 mg/l	
Soil	406.25 mg/kg	

#### 8.2. Exposure controls



#### Individual protection measures, such as personal protective equipment

##### Eye/face protection

Wear eye/face protection.

##### Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Tested protective gloves must be worn.

Suitable material: CR (polychloroprene, chloroprene rubber) NR (natural rubber, Natural latex) Butyl caoutchouc

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 2901

Revision date: 11.04.2024

Product code: 2901

Page 6 of 13

(butyl rubber)

Thickness of the glove material > 0,45mm

= 480 min. EN ISO 374

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

#### Skin protection

Use of protective clothing. Wear suitable protective clothing. The type of personal protection equipment has to be chosen based on the concentration and amount of the dangerous substance at the workplace.

#### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	blue green	
Odour:	Acetone	
Odour threshold:	No data available	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		56 °C
Flammability:		No data available
Lower explosion limits:		2,5 vol. %
Upper explosion limits:		14,3 vol. %
Flash point:		< -20 °C
Auto-ignition temperature:		535 °C
Decomposition temperature:		No data available
pH-Value:		not determined
Viscosity / kinematic:		not applicable
Water solubility:		completely miscible
Solubility in other solvents		not determined
Partition coefficient n-octanol/water:		No data available
Vapour pressure:		246 hPa
(at 20 °C)		
Vapour pressure:		814 hPa
(at 50 °C)		
Density (at 20 °C):		0.79 g/cm <sup>3</sup>
Relative vapour density:		not determined

### 9.2. Other information

#### Information with regard to physical hazard classes

Explosive properties

No data available

Oxidizing properties

No data available

#### Other safety characteristics

Evaporation rate: not determined

## SECTION 10: Stability and reactivity

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 2901

Revision date: 11.04.2024

Product code: 2901

Page 7 of 13

#### 10.1. Reactivity

No further relevant information available.

#### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

#### 10.3. Possibility of hazardous reactions

No known hazardous reactions.

#### 10.4. Conditions to avoid

Avoid dust formation.

#### 10.5. Incompatible materials

No further relevant information available.

#### 10.6. Hazardous decomposition products

Carbon dioxide (CO<sub>2</sub>) Carbon monoxide

### SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Toxicokinetics, metabolism and distribution

No data available

##### Acute toxicity

Based on available data, the classification criteria are not met.

##### ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
67-64-1	acetone; propan-2-one; propanone				
	oral	LD50 mg/kg 5800	Rat	J Toxicol Environ Health 15: 609-621 (19)	Undiluted acetone applied to female rats
	dermal	LD50 mg/kg > 7426	Rabbit	Toxicol Appl Pharmacol 7: 559-565. (1965)	other: Code of federal regulations: 21 C
	inhalation (4 h) vapour	LC50 76 mg/l	Rat		
68084-48-0	Copper(2+) neodecanoate				
	oral	LD50 mg/kg 2066	Rat	Study report (1977)	OECD Guideline 401

##### Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

##### Sensitising effects

Based on available data, the classification criteria are not met.

##### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

##### STOT-single exposure

May cause drowsiness or dizziness. (acetone; propan-2-one; propanone)

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 2901

Revision date: 11.04.2024

Product code: 2901

Page 8 of 13

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

#### Specific effects in experiment on an animal

No data available

#### Additional information on tests

No data available

#### Practical experience

May be harmful if swallowed, in contact with skin or if inhaled.

### 11.2. Information on other hazards

#### Other information

No information available.

#### Further information

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

## SECTION 12: Ecological information

### 12.1. Toxicity

Harmful to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
67-64-1	acetone; propan-2-one; propanone					
	Acute fish toxicity	LC50 mg/l	8120	96 h	Pimephales promelas	Publication (1984) OECD Guideline 203
	Acute crustacea toxicity	EC50 mg/l	8800	48 h	Daphnia pulex	Publication (1978) The toxicity of acetone towards daphnids
	Crustacea toxicity	NOEC mg/l	2212	28 d	Daphnia magna	Arch Environm Contam Toxicol 12: 305-310 Study conducted comparable to OECD 211 w
	Acute bacteria toxicity	(EC50 mg/l)	61150	0.5 h	activated sludge of a predominantly domestic sewage	Water Res 26: 887-892 (1992) ISO 8192
68084-48-0	Copper(2+) neodecanoate					
	Acute fish toxicity	LC50 mg/l	0.193	96 h	Pimephales promelas	Study report (1996) measurements were conducted by standard
	Acute algae toxicity	ErC50 mg/l	> 100	72 h	Raphidocelis subcapitata	Study report (1998) OECD Guideline 201
	Acute crustacea toxicity	EL50 mg/l	> 1000	48 h	Daphnia magna	Study report (1998) OECD Guideline 202
	Fish toxicity	NOEC mg/l	> 2.22	14 d	Oncorhynchus mykiss	Study report (2010) other: OECD 305
	Algae toxicity	NOEC mg/l	0.011	14 d	other algae: Marine macroalgae Fucus vesiculosis	Study report (2006) The study investigates the effects of di
	Crustacea toxicity	NOEC mg/l	4.78	7 d		Study report (1994) EPA OTS 797.1330



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 2901

Revision date: 11.04.2024

Product code: 2901

Page 9 of 13

#### 12.2. Persistence and degradability

No data available

#### 12.3. Bioaccumulative potential

No data available

#### **Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
67-64-1	acetone; propan-2-one; propanone	-0,23

#### **BCF**

CAS No	Chemical name	BCF	Species	Source
67-64-1	acetone; propan-2-one; propanone	3		Unpublished calculat
68084-48-0	Copper(2+) neodecanoate	< 225	Oncorhynchus mykiss	Study report (2009)

#### 12.4. Mobility in soil

No further relevant information available.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### 12.7. Other adverse effects

No data available

#### **Further information**

Avoid release to the environment.

## SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### **Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

##### **List of Wastes Code - residues/unused products**

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

##### **List of Wastes Code - used product**

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

##### **List of Wastes Code - contaminated packaging**

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

##### **Contaminated packaging**

Wash with plenty of water. Completely emptied packages can be recycled.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 2901

Revision date: 11.04.2024

Product code: 2901

Page 10 of 13

#### SECTION 14: Transport information

##### Land transport (ADR/RID)

**14.1. UN number or ID number:** UN 1090  
**14.2. UN proper shipping name:** ACETONE  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3



Classification code: F1  
 Limited quantity: 1 L  
 Excepted quantity: E2  
 Transport category: 2  
 Hazard No: 33  
 Tunnel restriction code: D/E

##### Inland waterways transport (ADN)

**14.1. UN number or ID number:** UN 1090  
**14.2. UN proper shipping name:** ACETONE  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3



Classification code: F1  
 Limited quantity: 1 L  
 Excepted quantity: E2

##### Marine transport (IMDG)

**14.1. UN number or ID number:** UN 1090  
**14.2. UN proper shipping name:** ACETONE  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3



Special Provisions: -  
 Limited quantity: 1 L  
 Excepted quantity: E2  
 EmS: F-E, S-D

##### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number or ID number:** UN 1090  
**14.2. UN proper shipping name:** ACETONE  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
 Hazard label: 3

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 2901

Revision date: 11.04.2024

Product code: 2901

Page 11 of 13



Limited quantity Passenger:	1 L	
Passenger LQ:	Y341	
Excepted quantity:	E2	
IATA-packing instructions - Passenger:		353
IATA-max. quantity - Passenger:		5 L
IATA-packing instructions - Cargo:		364
IATA-max. quantity - Cargo:		60 L

#### **14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

#### **14.6. Special precautions for user**

not applicable

#### **14.7. Maritime transport in bulk according to IMO instruments**

in delivery state not applicable

### **SECTION 15: Regulatory information**

#### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

##### **EU regulatory information**

Restrictions on use (REACH, annex XVII):  
Entry 3, Entry 40

Information according to 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

Marketing and use of explosives precursors (Regulation (EU) 2019/1148):

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

##### **National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

#### **15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

### **SECTION 16: Other information**

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 2901

Revision date: 11.04.2024

Product code: 2901

Page 12 of 13

#### Abbreviations and acronyms

CLP: Classification, labelling and Packaging  
 REACH: Registration, Evaluation and Authorization of Chemicals  
 GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals  
 UN: United Nations  
 CAS: Chemical Abstracts Service  
 DNEL: Derived No Effect Level  
 DMEL: Derived Minimal Effect Level  
 PNEC: Predicted No Effect Concentration  
 ATE: Acute toxicity estimate  
 LC50: Lethal concentration, 50%  
 LD50: Lethal dose, 50%  
 LL50: Lethal loading, 50%  
 EL50: Effect loading, 50%  
 EC50: Effective Concentration 50%  
 ErC50: Effective Concentration 50%, growth rate  
 NOEC: No Observed Effect Concentration  
 BCF: Bio-concentration factor  
 PBT: persistent, bioaccumulative, toxic  
 vPvB: very persistent, very bioaccumulative  
 ADR: Accord européen sur le transport des marchandises dangereuses par Route  
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 RID: Regulations concerning the international carriage of dangerous goods by rail  
 ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
 (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)  
 IMDG: International Maritime Code for Dangerous Goods  
 EmS: Emergency Schedules  
 MFAG: Medical First Aid Guide  
 IATA: International Air Transport Association  
 ICAO: International Civil Aviation Organization  
 MARPOL: International Convention for the Prevention of Marine Pollution from Ships  
 IBC: Intermediate Bulk Container  
 VOC: Volatile Organic Compounds  
 SVHC: Substance of Very High Concern  
 For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).  
 Flam. Liq: Flammable liquid  
 Acute Tox: Acute toxicity  
 Eye Irrit: Eye irritation  
 STOT SE: Specific target organ toxicity - single exposure  
 Aquatic Acute: Acute aquatic hazard  
 Aquatic Chronic: Chronic aquatic hazard

#### Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H336	Calculation method
Aquatic Chronic 3; H412	Calculation method

#### Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Kisling - 2901

Revision date: 11.04.2024

Product code: 2901

Page 13 of 13

H302	Harmful if swallowed.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

#### Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

#### Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	Adhesives and sealants	PW, C	6a, 6b, 12, 18, 19	1	11, 19	4, 8a, 8c, 8d	4e, 4g, 5c, 6g, 7c, 7g, 8, 10, 11, 13	110	K+D

LCS: Life cycle stages

SU: Sectors of use

PC: Product categories

PROC: Process categories

ERC: Environmental release categories

AC: Article categories

TF: Technical functions

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*